


## PLASTIC DRUM STANDARD PRODUCT DESCRIPTION

<b>Product Specification Number:</b> POK58X-XX-XX-XX-XX-XX		<b>Product Name:</b> <span style="font-size: 1.2em; font-weight: bold;">OK-58</span>			
<b>Regulatory Information:</b>  un 1H2/Y130/S (Test Report P238)  un 1H2/Z215/S (Test Report P239)	<b>Bill of Materials:</b>  <b>Body:</b> OK-58, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE)  <b>Cover:</b> Plain or Bung & Vent, HDPE. The B & V design has a 2" and a 3/4" NPS bung, with a vented 3/4" being available as an option. (NPS = National Pipe Straight thread)  <b>Lockband:</b> Side lever (SLL) or Bolt	<b>Product Illustration:</b> 			
<b>Nominal Capacity:</b> 58.0 U.S. Gallons	<b>Outage:</b> 2.4 U.S. Gallons	<b>Opening I.D.:</b> 20.7 inches	<b>Total Weight:</b> 22.7 lbs.		
<b>Actual Capacity:</b> 60.4 U.S. Gallons	<b>Outage %:</b> 4.1 %	<b>Nominal O.D.:</b> 23.2 inches	<b>Body Weight:</b> 19.0 lbs.		
<b>Export Cubes:</b> 11.02 cu. ft.	<b>Overall Height:</b> 36.8 inches	<b>Min. Wall Thickness:</b> 0.125 inches	<b>Chime Height:</b> 0.530 inches		
<b>Min. Blocking Diameter:</b> 22.8 inches	<b>Body Height:</b> 36.5 inches	<b>Mid Panel Height:</b> 12.9 inches			
<b>Special Notes:</b>					
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top;"> <p>1) Maximum filling temperature ~160°F. When filled at this maximum temperature drum should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum.</p> <p>2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1100 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums.</p> </td> <td style="width: 50%; vertical-align: top;"> <p>3) Handle with parrotbeak, side grabber, and sling.</p> <p>4) Recycle symbol embossed on bottom.</p> <p>5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.</p> </td> </tr> </table>				<p>1) Maximum filling temperature ~160°F. When filled at this maximum temperature drum should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum.</p> <p>2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1100 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums.</p>	<p>3) Handle with parrotbeak, side grabber, and sling.</p> <p>4) Recycle symbol embossed on bottom.</p> <p>5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.</p>
<p>1) Maximum filling temperature ~160°F. When filled at this maximum temperature drum should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum.</p> <p>2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 1100 lbs. each. Pallets should be of good quality that provides adequate support for plastic drums.</p>	<p>3) Handle with parrotbeak, side grabber, and sling.</p> <p>4) Recycle symbol embossed on bottom.</p> <p>5) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.</p>				
<p>Data, dimensions, and information provided on this document are considered as nominal values for general purpose use in evaluating this product for customer's application. These are not considered as manufacturing specifications. It is the responsibility of the customer or filler to select the appropriate packaging for use or resale, based on all information at their disposal, including specific application, regulatory compliance, product compatibility, transport, storage, and material handling requirements. Regulatory compliance for remanufacture, repair, or reuse of packaging is the responsibility of the reconditioner, customer and filler. Refer to appropriate regulations for packaging filling, transport, and storage requirements with your specific product.</p> <p>WE HEREBY DISCLAIM AND EXCLUDE ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.</p>					

Revision 1 : September 2003

Greif, Inc.  
425 Winter Road  
Delaware, Ohio 43015  
Phone (740) 549 6000  
www.greif.com